

US009409712B2

# (12) United States Patent Gieseke

## (10) Patent No.: US 9,409,712 B2 (45) Date of Patent: Aug. 9, 2016

(54)	APPARATUS FOR GRASPING, LIFTING AND	D
	MOVING A LARGE PANEL	

(76) Inventor: Gerald G. Gieseke, Selah, WA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 1 day.

(21) Appl. No.: 13/291,023

(22) Filed: Nov. 7, 2011

(65) **Prior Publication Data** 

US 2013/0113228 A1 May 9, 2013

(51) Int. Cl. *B65G 7/12* 

(2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

### (56) References Cited

#### U.S. PATENT DOCUMENTS

836,740 A *	11/1906	Dettenborn
1,215,350 A *	2/1917	Dietrich 294/86.4
1,837,425 A *	12/1931	Gastan 294/114
1,982,225 A *	11/1934	Miller 294/86.4
2,850,318 A *	9/1958	Mulhern 294/86.4
3,000,662 A *	9/1961	Scarlett 294/103.1

3,253,849		5/1966	Hansen 294/16
3,374,024	A *	3/1968	Reynolds 294/16
3,524,670	A *	8/1970	Ratomir 294/164
4,349,225	A	9/1982	Collins et al.
6,113,167	A *	9/2000	Mattis et al 294/16
6,494,513	B2 *	12/2002	Worthington 294/16
7.003.917	B2	2/2006	Hetherington et al.

<sup>\*</sup> cited by examiner

Primary Examiner — Dean Kramer (74) Attorney, Agent, or Firm — Floyd E. Ivey

#### (57) ABSTRACT

A panel gripping and lifting device (100) having a clamping assembly (105) having a handle assembly (162) rotatably interrelated with a spaced apart opposing jaw assembly (107) by a cam assembly (149). Jaws of the opposing jaw assembly (107) have a planar jaw inner surface (116); when the spacing between the jaws is increased, the planar jaws are fitted on either side of a panel; when the spacing between the jaws is lessened the planar jaws contact surfaces of the panel exerting a gripping force against the panel. When gripping forces are exerted against the panel the handle assembly (162) enables the lifting and moving of the panel such as seated multipane window (220) window frame (200) having an outwardly extending nail fin (210) or a sheet metal panel.

An alternative embodiment has opposing jaws rotating in the same plane and separated by jaw spacing. A first jaw and a second jaw are positioned on either side of a frame channel and, when the embodiment is rotated the jaw spacing is lessened causing the first jaw and the second jaw to clamp against the frame channel thereby allowing lifting of large framed units such as glass door units.

#### 14 Claims, 11 Drawing Sheets

